

# Operating grades at various height differences

Outside of standard dock leveler operating range - consult factory.

MAXIMUM HEIGHT DIFFERENTIAL (DOCK TO TRUCK BED)		in	2	4	6	8	10	12	14	16	18	20
		mm	51	102	152	203	254	305	356	406	457	508
<b>NOMINAL MODEL SIZES</b>	6' length: 5' x 6', 6' x 6', 6'6" x 6', 7' x 6'		2.6%	5.3%	8.0%	10.7%	13.3%	16.0%	18.7%	21.3%	24.0%	26.7%
	8' length: 6' x 8', 6'6" x 8', 7' x 8'		2.0%	4.0%	6.1%	8.1%	10.1%	12.1%	14.1%	16.2%	18.2%	20.2%
	10' length: 6' x 10', 6'6" x 10', 7' x 10'		1.6%	3.3%	4.9%	6.5%	8.1%	9.8%	11.4%	13.0%	14.6%	16.3%
	12' length: 6' x 12', 6'6" x 12', 7' x 12'		1.4%	2.7%	4.1%	5.4%	6.8%	8.2%	9.5%	10.9%	12.2%	13.6%

Maximum recommended grades: Hand Pallet Truck (3%)  Electric Pallet Truck (7%)  Electric Lift Trucks (10%)   
 Gasoline Trucks (15%)  Unusable