

'XDS' SERIES DOCK SAFETY PACKAGE

MODEL 'XDS4000' - HYDRAULIC SPECIFICATIONS:

Dock Leveler, Safety Barrier and Vehicle Restraint shall be hydraulic **Model** _____ comes complete with hydraulic lip and deck cylinders and 4" (101mm) assured motion float (maintained deck tilt) on dock leveler, 7.5" (190mm) high hydraulic roll-off guard/barrier, StrongArm™ SVR303 vehicle restraint, interior/exterior communications light package and driver warning signs as manufactured by BLUE GIANT.

MODEL	DECK WIDTH	DECK LENGTH w/ LIP	PIT DEPTH Front 20" and Rear 19 ½"	
			PIT WIDTH	PIT LENGTH
XDS4066	72"	75 ½"	74"	61 ¼"
XDS4068	72"	99 ½"	74"	85 ¼"
XDS40610	72"	123 ½"	74"	109 ¼"
XDS40612	72"	147 ½"	74"	133 ¼"
XDS40666	78"	75 ½"	80"	61 ¼"
XDS40668	78"	99 ½"	80"	85 ¼"
XDS406610	78"	123 ½"	80"	109 ¼"
XDS406612	78"	147 ½"	80"	133 ¼"
XDS4076	83"	75 ½"	85"	61 ¼"
XDS4078	83"	99 ½"	85"	85 ¼"
XDS40710	83"	123 ½"	85"	109 ¼"
XDS40712	83"	147 ½"	85"	133 ¼"

Capacities available: 30,000 / 35,000 / 40,000 / 45,000 / 50,000 / 60,000 / 80,000lb

For metric conversion to mm, multiply inches by 25.4. For conversion to kg, divide lb by 2.2.

TYPE:

Dock Leveler: Recessed, pit installed hinged dock leveler comes with automatically operated roll off guard/barrier. Electro-hydraulically operated with independent control of deck and lip.

Door and Dock Guard: Electro-hydraulic operated solid steel barrier incorporated into the deck. It is designed to protect forklifts from accidental roll-off when the overhead door is open, and protects overhead door panels and tracks from impact damage when the door is closed. Overall dimension is 7.5" (190mm) high x full width of deck less 6" per side x minimum 3/8" thick high tensile steel checker plate.

StrongArm™ SVR303 Vehicle Restraint: Electro-hydraulic operated non-impact design. Wall or ground mounted. Overall body dimensions 15 ½"W x 33"L x 8"H (394 x 838x 203mm).

OPERATION:

Dock Leveler: Hydraulic Operating System. Easy to operate, quiet, and smooth cycling. Electro-hydraulic raising and hydraulic lowering of the dock leveler controlled from a remote multi pushbutton station. Includes means of lowering the dock leveler below platform level with lip retracted behind dock bumpers. The loaded ramp's free fall is limited to not over 3" (76mm) by a hydraulic velocity fuse. Power pack controlling both leveler and restraint mounted underneath the deck. Operating system is 1HP totally enclosed non-ventilated (TENV) motor available in all standard voltages.

Door and Dock Guard: Hydraulic Operating System. Easy to operate, quiet, smooth and automatic cycling. Door and Dock Guard is kept in the upright position by upward biased spring tension and is retracted with power down hydraulics. Upon cycling of the dock leveler, the guard automatically retracts and lies flush with the deck, providing unobstructed flow of traffic. When the dock is cycled and returned to the stored position, the guard automatically returns to the upright position. Supervisor override keypad with indicator light is provided on the control station for end-loading and ground level hand bombing requirements.

StrongArm™ SVR303 Vehicle Restraint: Intelligent positioning system ensures proper communications and positive locking of the restraint arm.

Control Station: The Blue Genius™ Gold Series III is a multiple touch button control station with constant pressure "DECK", "LIP", "ENGAGE" and "RELEASE" touch buttons. It has a NEMA4X/IP65 (wet and corrosion resistant) rated polycarbonate enclosure. Overall dimensions 11¼"L x 7½"W x 5½"D (287 x 190 x 140mm) with programmable multi instructional languages.

Communication System: Interior red and green indicator lights mounted on the control station. Exterior LED red and green high visibility traffic style lights and direct and mirror image driver's warning signs. The lighting system alerts both dock attendant and vehicle driver to the status of the restraint. If vehicle has no restraining rear impact guard, the interior communication lights will flash yellow, warning the dock attendant that the vehicle is not secured and requires wheel chocks. Interior override indicator light for door and dock guard to signal guard is temporarily down during unique loading/offloading applications.

DOCK LEVELER FUNCTION:

Vertical Travel: Working range of 12" (305mm) above and 12" (305mm) below dock level.

Automatic Vertical Compensation: Unit provides float of 12" (305mm) above and 12" (305mm) below dock level.

Automatic Lateral Compensation: Provides 4" (101mm) assured motion float to compensate for canted vehicle beds.

Lip Operation: Hydraulically powered lip, controlled independently of main deck cylinder. Lip will yield under impact of incoming vehicle and will automatically drop pendant upon vehicle's departure. The length of the lip extension shall not be less than 16" (406mm) from the ramp edge.

Stop Button Function: For added safety, the control station has a 'STOP' touch button that will cause the deck and lip to stop in mid-motion when touched. The 'ESC' touch button activates the release function.

VEHICLE RESTRAINT FUNCTION:

Vertical Restraining Range: From 8" to 26" (203mm to 660mm) above grade, minimum 4" (101mm) contact required.

Horizontal Restraining Range: From 0" to 12" (305mm) beyond the face of the dock.

Mounting System: Dock face mounting using four (4) heavy duty wedge anchor bolts 3/4" dia. x 6" long (20 x 152mm). Transfer of pulling force to driveway improves restraining strength by equalizing forces on anchors. Trailer rear impact guard (ICC bar) during backing-in does not impact restraint's body.

RATED CAPACITIES / DESIGN:

Welding procedure compliant with ANSI AWS D1.1 (2008) specifications. All units rated in compliance with ANSI MH30.1 (2007). ANSI/NFPA70 approved electrical components. Dock Leveler capacities available from 30,000lb to 80,000lb (13,636kg to 36,363kg). Structural deck support to include minimum six each high-tensile solid steel I-beam members. Restraint rated at 35,000 lb (15,909kg) pull-out force and 100,000lb (45,454kg) mounting force. The Door and Dock Guard is rated to stop 10,000lb (4,545kg) rolling loads at 4 MPH (6 KMH).

VOLTAGE SELECTIONS:

- 115V / 1PH Range: 110-130 / 50-60Hz
- 230V / 1PH Range: 208-240 / 50-60Hz
- 230V / 3PH Range: 208-240 / 50-60Hz
- 460V / 3PH Range: 380-480 / 50-60Hz
- 575V / 3PH Range: 575-600/ 60Hz

SAFETY DEVICES:

- Supervisor keypad override
- Dock leveler and restraint interlocks to prevent cycle of dock until restraint engaged and to prevent release of dock until restraint returned to stored position
- Full operating range metal toe guard protection, painted in high visibility colours.
- Hydraulic velocity fuse "fall safe" to limit free fall up to 3" (76mm)
- Cross traffic support - lip engaged in saddles
- Corner safety stops
- Telescopic v-grooved maintenance strut, integral to unit
- Beveled lip
- Lights package (indoor/outdoor) with security features (activate / deactivate via code)
- Door interlock terminals, 24VDC provided

FINISH AND COLOR:

Dock Leveler: Toe guards painted safety yellow as specified by ANSI Z535.1. Remainder of unit painted blue. High visibility OSHA safety striping on stationary side toe guards. **Door & Dock Guard:** Painted high visibility safety yellow. **Vehicle Restraint:** Welded structural steel housing. Restraint arm is constructed of 1½" thick solid steel. The housing protects all components from damage from weather, dirt and debris. NEMA4 submersible rated wand switch, remote power pack location and cylinder vented to power pack reservoir protects from water damage. To resist corrosion and reduce maintenance, housing is zinc plated, main hinge pin is made of stainless steel and cylinder rod has nitride coating. **LED Traffic Lights:** The housing shall be one-piece, weatherproof constructed and made of ultra high molecular weight plastic. The lights shall be 4" (101mm) diameter for red and green. Overall body 5"W x 11½"L x ½"D (127 x 292 x 13mm) in size.

WARRANTY:

Warranties are subject to standard limitations on liability. Please consult Blue Giant warranties at <http://www.BlueGiant.com> for full details on warranty information and product registration.

STANDARD ACCESSORIES:

- Night Locks
- Two model DB411 laminated bumpers 14"W x 10"H x 4.5"D (355 x 254 x 114mm)
- Blue Genius™ advanced communication package (includes LED interior red/yellow/green and exterior red/green traffic lights and driver warning signs) with security features (activate / deactivate via code)
- Wall bracket for restraint power pack and 24' (7,315mm) hydraulic hose
- Manual override (to lower the restraining arm in event of power failure)
- Four mounting bolts
- Communications package; lights and signs

OPTIONAL ACCESSORIES:

- Foam insulation underside of deck - dock
- Side and rear rubber style weather seals – dock
- Side and rear nylon brush style weather seals – dock
- 18" (457mm) long lip
- 20" (508mm) long lip
- 24" (609mm) long lip
- Remote mounted power pack on 24' (7,315mm) hydraulic hose - dock
- Pour-in pan (dock leveler welded to a steel pan, allowing it to be "poured in place" after concrete slab is poured)
- Clean pit frame - dock
- Extension plates to suit extended dock leveler pits - restraint
- Overhead door interlock photo sensor (24VDC)
- Standard oil (temperature range of -41 to 200°C)
- Arctic oil (temperature range of -57 to 150°C)-recommended for temperatures below minus 7°C / 18°F
- Biodegradable oil (temperature range of -36 to 230°C)in lieu of standard hydraulic oil –environmentally friendly